

Specifications



Revoria Press EC2100/EC2100S Full Configuration



Full Configuration: W 10462 x D 1104 x H 1786 mm

Various options available according to needs

Feeding options



High Capacity Feeder C3-DS + Multi Sheet Inserter for banner print

- Air assist • Multi-feed detection

2100 sheets x 2 trays + 250 sheets
Maximum SRA3, 330 x 660 mm



2nd High Capacity Feeder C1-DS + High Capacity Feeder C3-DS + Multi Sheet Inserter for banner print

- Air assist • Multi-feed detection

2100 sheets x 4 trays + 250 sheets
Maximum SRA3, 330 x 660 mm



Air Suction Feeder C1-DS*1

- Air suction
- Multi-feed detection

2200 sheets x 2 trays + 250 sheets
Maximum SRA3, 330 x 660 mm



Chained Air Suction Feeder C1-DS-L*1 + Chained Air Suction Feeder C1-DS-R

- Air suction • Multi-feed detection

2200 sheets x 2 trays + 250 sheets
Maximum SRA3, 330 x 660 mm



Air Suction Feeder C1-DSXL*1 + Banner Unit for Air Suction Feeder C1-DSXL

- Air suction • Multi-feed detection
- Long sheets feeding

900 sheets + 2200 sheets + 250 sheets
Maximum SRA3, 330 x 1300 mm (Upper tray)



Chained Air Suction Feeder C1-DSXL-L*1 + Chained Air Suction Feeder C1-DS-R + Banner Unit for Air Suction Feeder C1-DSXL

- Air suction • Multi-feed detection
- Long sheets feeding

900 sheets + 2200 sheets x 3 trays + 250 sheets
Maximum SRA3, 330 x 1300 mm (Left Upper tray)

Output options

1 Interface Decurler Module D1

- Real-time paper curl correction

2 Inserter D1

- Cover / sheet insertion

3 Static Eliminator D1

- Eliminate static electricity

4 Smart Monitoring Gate D1

- Real-time smart print optimisation

5 High Capacity Stacker A1

- 5000-sheet offset-stacking
- Stacker cart
- Long sheets output*2
- 2 x high capacity stackers possible

6 Crease/Two-sided Trimmer D2

- Two-sided trim • Crease

7 Folder Unit CD2

- Z Fold half sheet • Tri-fold

8 Finisher D6 with Booklet Maker

- Sort / Stack • Stapling
- Hole punch*2 • Single fold
- Saddle staple
- Long sheets output

Finisher D6

- Sort / Stack • Stapling
- Hole punch*2
- Long sheets output

9 Square Back Fold Trimmer D1


- Face trim • Square back

Folder Unit CD3

- Z Fold half sheet • Tri-fold
- For C5 Finisher

Offset Catch Tray

Offset stack



Long Catch Tray

Long sheets output



*1: Multi Sheet Inserter for Banner Print is equipped as standard
*2: Optional

Revoria Press EC2100/EC2100S Specifications

Item	Description
Colour capability	Full colour
Print resolution	2400 x 2400 dpi
Warm-up time	300 seconds or less (room temperature 23°C)
Continuous print speed*1	A4: 100 ppm, A3: 55 ppm
Paper size*2	Tray 1, 2, 3 140 x 182 mm to 330 x 488 mm
Paper weight	Tray 1, 2, 3 64 to 256 g
Paper capacity*3	Tray 1, 2, 3 570 sheets x 3-tray
Power supply	Single-phase AC200-240 V +/-10%, 24 A, 50/60 Hz, ground connection
Maximum power consumption	5.76 kW (in case of 240 V)
Dimensions*4	W 1679 x D 834 x H 1370 mm
Weight*5	492 kg or less

Note : The printer main unit must be connected to the paper feed option. You must also use the output option.

*1: When continuously printing a single sided document. 52 to 300 g, uncoated paper. Print speed may be reduced depending on conditions of output data, on whether specialty toner is used, on whether auto image quality adjustment is performed, on whether the job includes a mixture of paper sizes and types, and other reasons.

*2: Image loss width: lead edge 4.0 mm, trail edge 2.0 mm, front 2.0 mm, rear 2.0 mm.

*3: 82 g paper

*4: Printer unit only. Excludes paper feeding / output options.

*5: Printer unit only. Excludes paper feeding / output options. Excludes toner cartridges.